

WorkCentre®

5735/5740/5745/5755/5765/5775/5790

Black-and-White Multifunction System



WorkCentre 5735/5740/5745/5755
shown with Duplex Automatic Document Handler with High Capacity Tandem Tray and Offset Catch Tray



WorkCentre 5735/5740/5745
shown with Duplex Automatic Document Handler with High Capacity Tandem Tray and Basic Office Finisher



WorkCentre 5735/5740/5745/5755/5765/5775
shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray and Office Finisher



WorkCentre 5740/5745/5755/5765/5775/5790 shown with Duplex Automatic Document Feeder, High Capacity Tandem Tray, High Capacity Feeder and High Volume Finisher with Folder and Booklet Maker and Post Process Inserter

Output Speed			
	8.5 x 11 in. (A4/210 x 297 mm)	8.5 x 14 in. (216 x 356 mm)	11 x 17 in. (A3/297 x 420 mm)
WorkCentre 5735:	Up to 35 ppm (pages per minute)	Up to 25 ppm	Up to 21 ppm
WorkCentre 5740:	Up to 40 ppm	Up to 36 ppm	Up to 31 ppm
WorkCentre 5745:	Up to 45 ppm	Up to 36 ppm	Up to 31 ppm
WorkCentre 5755:	Up to 55 ppm	Up to 36 ppm	Up to 31 ppm
WorkCentre 5765:	Up to 65 ppm	Up to 49 ppm	Up to 42 ppm
WorkCentre 5775:	Up to 75 ppm	Up to 49 ppm	Up to 42 ppm
WorkCentre 5790:	Up to 90 ppm	Up to 54 ppm	Up to 46 ppm
First-image-out Time (FCOT) – letter size, from platen to offset catch tray			
	WorkCentre 5735: As fast as 4.7 seconds WorkCentre 5740/5745/5755: As fast as 3.4 seconds WorkCentre 5765/5675/5790: As fast as 2.7 seconds		
Copy Specifications			
Copying			
Document Scanner	Platen (available only on 5735) Duplex Automatic Document Handler (DADH) 75-sheet capacity (5735) Duplex Automatic Document Handler (DADH) 100-sheet capacity (5740/5745/5755/5765/5775/5790) Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF		
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 9,999		

Resolution	600 x 600 dpi input / 4800 x 600 dpi interpolated output	
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)	
Copy Pre-Collation Memory (EPC)	384 MB (expandable to 1 GB with additional Memory Kit)	
Basic Copy Features/Options	Features Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Options Hole Punching Stapling Booklet Creation (optional with High Volume Finisher) Post Process Inserter (optional with High Volume Finisher) C/Z Folding (optional with High Volume Finisher)
Imaging Copy Features	Image Quality <ul style="list-style-type: none"> • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)	
Output Copy Features	ID Card Copy Booklet Creation Inserts and Tab copying Covers (Front only, Front and Back, Back only: Blank or Printed) Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Annotation and Bates Stamping Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Sample Set and Job Storage (Store and Recall job programming) Transparencies (including dividers – blank or printed) Heavy weight paper (not rough stock)	
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Onboard Documentation Languages (Select up to 21 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Catalan, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)* * Language selection and number varies by location	
Reduction/Enlargement	Variable Zoom from 25 % - 400 % in 1 % increments Six User-Programmable percentages (25 %, 64 %, 78 %, 129 %, 154 % and 200 %)	
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service	
USB Port	Xerox Copier Assistant® Customer device administration/software upgrade Common Access Card Enablement	
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.	
Paper Handling – Duplex Automatic Document Handler (DADH) (Optional with 5735, standard on 5740/5745/5755/5765/5775/5790)		
Capacity ¹	5735: 75 sheets 5740/5745/5755/5765/5775/5790: 100 sheets	

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Speed	5735A/5740A/5745A/ 5755A (Color Scanner)	5765/5775/5790 with Black and white Scanner	5765/5775/5790 with Color Scanner
8.5x11 (A4/210 x 297 mm) LEF	Up to 80 ipm	Up to 80 ipm	Up to 80 ipm
Paper Sizes Sensed	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF)) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF		
Weights	13 lb to 42 lb bond (50 to 160 gsm)		
Paper Handling – Trays 1-2			
Capacity ¹	500 sheets each		
Sizes	User Adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)		
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Custom Settings (up to 7)		
Options	Envelope Tray Kit for Tray 2 (Capacity 50 envelopes)		
Paper Handling – Bypass Tray			
Capacity ¹	100 sheets		
Sizes	Custom sizes: 4.25 x 5.5 in. (A6) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 58 lb bond (60 to 216 gsm)		
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Custom Settings (up to 7)		
Paper Handling – High Capacity Tandem Tray (Optional with 5735/5740/5745, standard with 5755/5765/5775/5790)			
Capacity ¹	Two trays: 1,600 and 2,000 sheets		
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF		
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)		

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Paper Handling – High Capacity Feeder (Optional with 5735/5740/5745/5755/5765/5775, required with 5790)			
Capacity ¹	4,000 sheets		
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF Optional 8.5 x 11 / 8.5 x 14 Short Edge Feed Kit – 8.5 x 14 in. (A4/210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 Short Edge Kit – 11 x 17 in. (A3/297 x 420 mm) SEF with 2,000 sheet capacity		
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)		
Paper Handling – Total Capacity			
Device Total Capacity ¹	8,700 sheets (with Bypass Tray, front loading paper trays, High Capacity Tandem Tray and High Capacity Feeder)		
Output Option - Offset Catch Tray (Optional with 5735/5740/5745/5755)			
Capacity ¹	300 sheets		
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)		
Output Option - Basic Office Finisher (Optional with 5735/5740/5745)			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 1,000 sheets		
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)		
Stapling ¹	30 sheets Single position (top left hand corner)		
Output Option – Office Finisher (Optional with 5735/5740/5745/5755/5765/5775)			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 2,000 sheets		
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)		
Stapling ¹	50 sheets Single (any corner) and dual		
Hole Punch (Optional)	<table border="0"> <tr> <td style="vertical-align: top;">North America 3-hole punch 2-hole Legal punch</td> <td style="vertical-align: top;">Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch</td> </tr> </table>	North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch
North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch 4-hole “Swedish” punch		
Output Option – High Volume Finisher Option (Optional with 5740/5745/5755/5765/5775/5790)			
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets		
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)		
Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch		

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Hole Punch (Optional)	North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch
Output Option – High Volume Finisher with Booklet Maker (Optional with 5740/5745/5755/5765/5775/5790)		
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets	
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch	
Hole Punch (Optional)	North America 3-hole punch 2-hole Legal punch	Europe 2-hole punch 4-hole punch and 4-hole “Swedish” punch
Booklet Maker Capacity ¹	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Stapling ¹	Saddle-stitch (2-15 sheets / 8-60 page booklet)	
Folding	V-folding (1-15 sheets / unstapled)	
Output Option – Z-Fold / C-Fold Unit with HVF with Booklet Maker (Optional with 5740/5745/5755/5765/5775/5790)		
Capacity ¹	50 sheets or unlimited capacity with tray stop in the down position	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Output Option – Post Process Inserter (Optional with HVF and HVF with Booklet Maker)		
Capacity ¹	250 sheets	
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)	
Output Option – Convenience Stapler Option		
Capacity ¹	50 sheets	
Print Specifications		
Network Printing – Controller (Simultaneous rip, receive, program ahead, queue processing and transmit) - Standard on all configurations		
Processor	1.2 GHz Freescale dedicated	
Memory (ESS)	640 MB (expandable to 1 GB with additional Memory Kit)	
System Disk	160 GB hard drive shared	

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Printer Language (PDL) auto switching	<ul style="list-style-type: none"> • PCL 6/PCL 5e • PostScript 3 emulation • TIFF (6.0 Old JPEG and New JPEG) • TIFF Fax Extended (TIFF-FX) • PDF • LCDS, SCS, XES and IPDS through third party transforms
Network Printing – Resolution (printing via CentreWare® software)	
	PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey) PCL: 600 x 600 dpi Supports PCL and PS switching within job
Network Printing – Printing Features	
Advanced features	Bi-directional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop
Paper Output	Special font, Banner Sheet, Rotate Image, Offset
Network Printing – Print Driver Options	
Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay • LAN Fax-with fax option • Save and Save & Print Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch (if configured) • Booklet creation • Fit to new paper size • Saddle stitch with High Volume Finisher with Booklet Maker • Z-Fold / C-Fold Unit with High Volume Finisher with Booklet Maker Output tray selections Store and recall driver setting
Special Pages	Exception Page programming (covers, inserts/tabs, exception pages)
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)
Layout/Watermark	N-up (16) / Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options
Printing Protocols and Networks	
Physical	Ethernet 10/100/1000Base-T, IEEE802.5 (Token ring) [via third party adapter], Wireless Ethernet (IEEE802.11a/b/g) [via third party adapter], USB print

Operating Systems	<ul style="list-style-type: none"> • Microsoft® Windows®, XP, Vista, Windows 7, Windows Server 2003, Windows Server 2008 • Novell® NetWare 5.x, 6.x • Mac® OS® 10.4, 10.5, 10.6 • Solaris 8, 9, 10 SPARC, Solaris 10x86 • HP-UX® 11iv2 • IBM® AIX 5 v5.3 • Linux Fedora Core 1-9 • Red Hat® Enterprise Linux® 4 • open SUSE® 10/11 		
Network Protocols	<ul style="list-style-type: none"> • TCP/IPv4/IPv6, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP • AppleTalk/EtherTalk 		
Administration Protocols	DHCP, BOOTP, SNMP, WINS, Bonjour, DDNS, SLP v2, SSDP, HTTP/S, RARP, LDAP, SMTP, POP3		
Security Protocols/Features	Protocols <ul style="list-style-type: none"> • HTTPS • IPsec • 802.1X • SNMPv3 	Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption 	
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment Windows XP (32 and 64 Bit), Windows 7, Windows Server 2003/2003 64 Bit, Windows Vista/Vista 64 Bit, Windows Server 2008, Microsoft Certified	PCL6/5e Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs 	PostScript 3 Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Mac OS 10.4 - Generic PPD	N/A	Generic PPD
	Mac OS 10.5, 10.6 - Xerox custom	N/A	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Toner, Fuser and Xerographic module status
Xerox Mobile Express Driver®(X-MED)	Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Xerox Global Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		

Print Submission Tools	Environment Solaris 8, 9, 10 SPARC, Solaris 10x86; HP-UX® 11.0, 11iv2, IBM® AIX 5 v5.3; Linux Fedora Core 1-9; Red Hat® Enterprise Linux® 4; open SUSE® 10/11	PCL N/A	PostScript 3 Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows® XP, Windows Server 2003, Windows Server 2008, Windows Vista	N/A	Submission Tool for any TIFF or PDF file (via web only)
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2		
Xerox CentreWare® Internet Services	Allows simple remote installation setting of configuration options and management of the device		
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher		
Novell NDPS/NEPS (gateway for WorkCentre)	Server gateway application: centralized management tool		
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View		
Xerox CentreWare for Tivoli NetView	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by Tivoli NetView		
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView		
Xerox Barcode Pro PS <i>Information available at www.xeroxofficesap.solutions.com</i>	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.		
Xerox Device Types for SAP R/3 Environment <i>are available at www.xeroxofficesap.solutions.com</i>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre • Network Accounting (JBA) – Provides capability to add Job Based Accounting User IDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net 		
Xerox SAP R/3 Intelligent Barcode Utility (optional) <i>Purchase via www.font.net</i>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.		

CentreWare Internet Services – Integrated device Web page			
Device Status	Web server embedded on Controller <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts 		
Job-Print Queue Viewing	Complete job print queue management		
Job Submission	Print ready files PS, PCL (TIFF, PDF with Copier/Printer only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning		
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x, 7.x Safari 1.x Mozilla Firefox 1.x		
Support	Online support available via web page		
Scan Specifications			
Scanning (Color scanning available at time of purchase ²)			
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs		
Speed	5735A/5740A/5745A/ 5755A (Color Scanner)	5765/5775/5790 with Black and white Scanner	5765/5775/5790 with Color Scanner
8.5x11 (A4/210 x 297 mm) LEF	Up to 80 ipm	Up to 80 ipm	Up to 80 ipm
Resolutions	DPI Options 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi		
	Scan Presets <ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200 		
	Quality/File Size <ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size) 		
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)		

² For 5765 / 5775 / 5790: Color Scan option can be selected at time of purchase or may be added later as an upgrade option.

³ JPEG only available with Color Scanning

File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG ³ compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression), PDF/A, XPS, Searchable PDF, PDF/A Searchable XPS
Network Scanning	
Capability	<ul style="list-style-type: none"> • Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services • Scan to Home displays one template and populates with the user's directory path after authentication • Scan to file • Scan to network server / directory • Scan to Mailbox • Scan to Folder on hard disk for device access of documents • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com • Color scanning (optional)
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template • Metadata Fields consists of field name, display at the LUI or not, default value and other configurations Customized fields viewed on user interface Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job for Scan to file and Scan to Email (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.
Scan to Email	
Capability	Scan to Email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options
Network Scanning Software Solutions	
Scan to PC Desktop Workgroup Edition SE (optional)	A desktop offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort SE – image viewing and file management software ScanSoft OmniPage SE – offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops
Scan to PC Desktop Workgroup Edition Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools. ScanSoft PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> • Complete PDF functionality • Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability.

³ JPEG only available with Color Scanning

SMARTsend ⁴ (optional)	<p>Server base document routing software that supports multiple scan-enabled multifunctional systems Enables transformation, distribution and routing of scanned documents Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary)</p> <ul style="list-style-type: none"> • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site <p>Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information</p>
SMARTsend ⁴ Professional (optional)	<p>Everything in SMARTsend, plus:</p> <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Searchable PDF • Scan to Internet fax file destination • TrueMatch patented search technology
Fax Specifications	
Fax Options – Walkup Option (One or Two Lines Options)	
Compatibility	ITU (CCITT) Group 3
Memory	256 MB (One Line and Two Line options)
Speed/Modem(s)	1 or 2 V.34 modems: 33kbps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/JBIG/G3/Super G3
Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax – off Platen, mixed sizes or Bound/Book <p>Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce/Split large documents Cover letter Delayed send Build Job (up to 1000 images) Polling</p>
Fax Receive Features	<p>One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header)/Auto Auto answer delay Secure receive Junk fax prevention Fax Forward to Email and File</p>
Fax Reports	<p>Activity Dial directory Group directory Options Pending Jobs</p>
Fax Mailboxes	<p>Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected</p>

⁴ Features, configurations and options vary by location.

<p>Auto Dialing Features</p>	<p>Speed Dials</p> <ul style="list-style-type: none"> • 200 (One-line option) • 1,000 (Two-line option) <p>Group Dials:</p> <p>One-line Option:</p> <ul style="list-style-type: none"> • Up to 100 groups • Up to 200 recipients per group • Up to recipient entries: 200 <p>Two-line option:</p> <ul style="list-style-type: none"> • Up to 200 groups • Up to 400 recipients per group • Up to 1000 recipient entries <p>Auto redial</p> <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
<p>Resolutions</p>	<p>200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi 200 x 400 dpi 400 x 400 dpi 400 x 600 dpi 600 x 600 dpi (Super Fine)</p>
<p>Fax Options – LAN Fax with Walkup Fax (Optional)</p>	
	<p>Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers) Recipient options (add recipient or add from phone book) User personal phone book – up to 1,000 entries Confirmation sheet Send speed (14.4/33.6kbps or 4800bps) Send time Dialing options (prefix or credit card) Cover sheet (add notes) Preferences – Phonebook (personal or shared LDAP)</p>
<p>Fax Options – Internet Fax Enablement (Standard)⁵</p>	
<p>Capability</p>	<p>Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients</p>
<p>Maximum Scan Area</p>	<p>11 x 17 in. (A3/297 x 420 mm)</p>
<p>Address Directory Access</p>	<p>Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book</p>
<p>File Formats</p>	<p>TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF</p>
<p>Resolutions</p>	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi</p>

⁵ Not available on 5735/5740/5745/5755/5765/5775/5790 Copier

Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 compliant
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body
Fax Options – Network Fax Server Enablement (Standard)⁵	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm)) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com
Device Management Specifications	
Accounting Features – Xerox Standard Accounting (Standard with Copier/Printer/Scanner, not available with Copier only configurations)	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print. Xerox Standard Accounting can be used in conjunction with an external device via the FDI (e.g. Coin Op or Card Reader).
Accounting Features – Network Accounting Enablement Kit (Optional)	
	Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Business Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

⁵ Not available on 5735/5740/5745/5755/5765/5775/5790 Copier

Security – Review the Supplemental Security Brochure for Details	
Authentication	Secure device login with network user name and password Supports Kerberos (Windows® 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) LDAP Secure Access
Features	802.1X Compliant IPv6 Ready (Phase 2) Disk Image Overwrite – Immediate, On Demand, Scheduled HTTPS (SSL) SNMP V3 IPsec Network Authentication Device Access Password Protection IP Filtering Audit Log Full Disk Encryption Secure Print Fax Security
Common Criteria Certification	Common Criteria Certification provides independent, objective validation of the reliability, quality, and trustworthiness of IT products. It is a standard that customers can rely on to help them make informed decisions about their IT purchases.
Secure Access Unified ID System® (Optional)	
	Secure Access Unified ID System adds an advanced layer of security at the device by enabling users to log-in to a Xerox MFP system with a swipe of their magnetic or proximity ID card. When combined with Follow-You Print™ functionality, Secure Access allows private print jobs to be accessed from any Xerox printer or MFP on your network.
Common Access Card Enablement	
	Common Access Card Enablement is a solution that increases security of government facilities and critical information through the use of smart identification cards. (Available only in U.S. and certain configurations.)
Xerox Extensible Interface Platform® (EIP)	
	Xerox EIP acts as a gateway, enabling simplified, server-based applications that personalize the user experience through customized touch-screen displays. Personalized for each user. These applications will yield simpler user interactions and result in less time interacting with the MFP which drives increased worker productivity and systems that easily adapt to your business processes. For example, combined with the optional SMARTsend® solution, you can set up a digital repository for users to browse and print frequently requested documents.
Machine Specifications	
Monthly Duty Cycle	
	5735 – up to 125,000 pages 5740 – up to 150,000 pages 5745 – up to 175,000 pages 5755 – up to 200,000 pages 5765 – up to 250,000 pages 5775 – up to 300,000 pages 5790 – up to 400,000 pages
Basic Configurations ⁴	
	WorkCentre with Platen, Trays 1-2 and Stand (5735) WorkCentre with DADH, Trays 1-2 and Stand (5735/5740/5745) WorkCentre with DADH, Trays 1-2, High Capacity Tandem Tray (Available with all configurations)

⁴ Features, configurations and options vary by location.

Accessory Options ⁴							
Stand (Standard with 5735/5740/5745) High Capacity Tandem Tray (standard with 5755/5765/5775/5790) High Capacity Feeder Optional 8.5 x 11 / 8.5 x 14 Short Edge Kit for High Capacity Feeder Optional 11 x 17 Short Edge Kit for High Capacity Feeder Offset Catch Tray (5735/5740/5745/5755) Basic Office Finisher (5735/5740/5745) Office Finisher (5735/5740/5745/5755/5765/5775) High Volume Finisher (5740/5745/5755/5765/5775/5790) High Volume Finisher with Booklet Maker (5740/5745/5755/5765/5775/5790) High Volume Finisher with Booklet Maker and Z-Fold/C-Fold unit (5740/5745/5755/5765/5775/5790) Post Process Inserter (Optional with High Volume Finishers) Convenience Stapler Hole Punch (with Office Finisher and High Volume Finisher – see Output Options for details) Envelope Tray Kit (in place of Tray 2) Foreign Interface Device (FDI) Xerox Copier Assistant® (XCA) Walkup Fax with LAN Fax: One line and Two lines Scan to PC Desktop® SE and Professional Enablement for Network Accounting and Xerox Alliance Partner Solutions Color Scanning Kit Xerox Unicode International Printing Kit Common Access Card Enablement 1 GB Memory Kit Copier to Copier/Printer/Scanner Upgrade							
Electrical Requirements							
5735/5740/5745/5755:	110-140 Volt Nominal, 60 Hz, 15A (North America) 220-240 Volt Nominal, 50 Hz, 10A (Europe)						
5765/5775/5790:	110-140 Volt Nominal, 60 Hz, 20A (North America) 220-240 Volt Nominal, 50 Hz, 10A (Europe)						
Note: Convenience Stapler requires separate 110V 15A (North America) / 220-240V 10A (Europe) circuit							
Power Consumption							
	5735 ⁶	5740 ⁶	5745 ⁶	5755 ⁶	5765 ⁶	5775 ⁶	5790 ⁷
Running	≤ 1130 watts	≤ 1130 watts	≤ 1230 watts	≤ 1330 watts	≤ 1640 watts	≤ 1690 watts	≤ 1840 watts
Standby	≤ 300 watts	≤ 300 watts	≤ 300 watts	≤ 300 watts	≤ 320 watts	≤ 320 watts	≤ 340 watts
Low Power Mode	≤ 125 watts	≤ 125 watts	≤ 125 watts	≤ 125 watts	≤ 160 watts	≤ 160 watts	≤ 160 watts
Auto Off / Sleep mode	≤ 15 watts	≤ 15 watts	≤ 15 watts	≤ 15 watts	≤ 15 watts	≤ 15 watts	≤ 15 watts
Warm up Ready to Copy	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds
Warm up Ready to Print	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds	≤ 30 seconds
Low Power Recovery	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds	≤ 9 seconds
Environmental Considerations							
Required Temperature Range	10° to 32° C						
Required Relative Humidity	10% to 85%						

⁴ Features, configurations and options vary by location.

⁶ With Office Finisher

⁷ With High Volume Finisher

Dimensions and Weights (5735/5740/5745/5755)				
	Width ⁸	Depth	Height	Weight ⁹
Configuration with Offset Catch Tray	51 in. / 1,290 mm	26 in. / 645 mm	45 in. / 1,147 mm	273 lbs / 124 kg
Configuration with Basic Office Finisher (5735/5740/5745)	60 in. / 1,524 mm	26 in. / 645 mm	45 in. / 1,147 mm	324 lbs / 147 kg
Configuration with Office Finisher	60 in. / 1,524 mm	26 in. / 645 mm	45 in. / 1,147 mm	335 lbs / 152 kg
With High Volume Finisher (5740/5745/5755)	77 in. / 1,960 mm	26 in. / 645 mm	45 in. / 1,147 mm	430 lbs / 195 kg
With High Volume Finisher with Booklet Maker (5740/5745/5755)	78 in. / 1,985 mm	26 in. / 645 mm	46 in. / 1,180 mm	488 lbs / 222 kg
With High Volume Finisher with C/Z Folder and Post Process Inserter (5740/5745/5755)	91 in. / 2,310 mm	26 in. / 645 mm	46 in. / 1,180 mm	550 lbs / 250 kg
High Capacity Feeder	15 in. / 389 mm	26 in. / 645 mm	23 in. / 575 mm	66 lbs / 30 kg

Dimensions and Weights (5765/5775/5790)				
Configuration with Office Finisher (5765/5775)	60 in. / 1,524 mm	28 in. / 704 mm	45 in. / 1,147 mm	344 lbs / 156 kg
With High Volume Finisher	77 in. / 1,960 mm	28 in. / 704 mm	45 in. / 1,147 mm	441 lbs / 200 kg
With High Volume Finisher with Booklet Maker	78 in. / 1,985 mm	28 in. / 704 mm	46 in. / 1,180 mm	500 lbs / 227 kg
With High Volume Finisher with C/Z Folder and Post Process Inserter	91 in. / 2,310 mm	28 in. / 704 mm	46 in. / 1,180 mm	568 lbs / 258 kg
High Capacity Feeder	15 in. / 389 mm	28 in. / 704 mm	23 in. / 575 mm	66 lbs / 30 kg

Noise Levels ¹⁰							
	5735	5740	5745	5755	5765	5775	5790
Standby dB (A) SPL	35	35	35	35	35	35	35
Run Continuous dB (A) SPL	54	55	56	56	57	57	58
Run Impulse dB (A) L SPL	57	58	59	61	62	62	63

Certifications	
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 2004/108/EC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 2006/95/EC (Europe) 95/5/EEC (Europe) ENERGY STAR ^{®11} Blue Angel Certified Full system Common Criteria (ISO 15408) Certified

⁸ Includes Shelf

⁹ Weights do not include Shelf (2.99 lbs. / 1.36 kg)

¹⁰ Noise levels shown are "Not to Exceed" levels. Actual noise levels will be lower.

¹¹ For 5700 Series Printer/Copier and Printer/Copier/Scanner configurations. Includes Copier-Only configuration if fax is installed.

Supplies				
	Description	Order Number	No. per Box	Expected Yield
	Toner Cartridge 5735 - 5755	006R1046	2	> 36,000 per cartridge at 6 % area coverage > 50,000 per cartridge at 6 % area coverage
	5765 - 5790	006R1146	2	
	Waste Toner Bottle (supplied with each toner cartridge box)	008R12896	1	100,000
	Staple Cartridge (for Basic Office Finisher)	108R00682 108R00535	1 3	3,000 per cartridge 3,000 per cartridge (9,000 staples)
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for HVF with Booklet Maker – saddle-stitch stapling)	008R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
	Staple Cartridge (for Convenience Stapler) • Complete Cartridge • Refill Cartridge	008R12964 008R12941	1 3	5,000 per cartridge 5,000 per cartridge (15,000 staples)
	Staple Cartridge (for HVF and HVF with Booklet Maker) • Complete Cartridge • Refill Cartridge	008R12912 008R12898	1 3	5,000 per cartridge 5,000 per cartridge (15,000 staples)

Smart Kits				
	Description	Order Number	No. per Box	Expected Yield
	Fuser Module (includes ozone filter)			
	5735 - 5755:			
	North America:	109R00752	1	400,000
	Europe:	109R00751	1	400,000
	5765 - 5790:			
	North America:	109R00773	1	400,000
	Europe:	109R00772	1	400,000
	Xerographic Module – Metered			
	5735:	113R00608	1	200,000
	5740 - 5790:	113R00672	1	400,000 – 500,000
	Xerographic Module – Sold			
	5735:			
	North America:	113R00610	1	200,000
	Europe:	113R00607	1	200,000
	5740 - 5790:			
	North America:	113R00674	1	400,000 – 500,000
	Europe:	113R00673	1	400,000 – 500,000
	Document Handler Feeder Rolls			
	5735:	113R00717	1	150,000 feeds
	5740 - 5790:	113R00718	1	150,000 feeds



For 5700 Series Printer/Copier and Printer/Copier/Scanner configurations.
Includes Copier-Only configuration if fax is installed.

For more information, call 1-800-ASK-XEROX or visit us at www.xerox.com/office

