

Xerox® Colour C60/C70 Printer

Colour Multifunction Printer

To interactively build and configure your own Xerox® Colour C60/C70, please visit www.buildyourownxerox.com.



Xerox® Colour C60 Printer			Xerox® Colour C70 Printer	
Simplex Speeds	Colour	Black and white	Colour	Black and white
A4 64 to 105 g/m ² uncoated 106 to 176 g/m ² uncoated 106 to 150 g/m ² coated 151 to 300 g/m ² uncoated 151 to 300 coated	Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
A3 64 to 105 g/m ² uncoated 106 to 176 g/m ² uncoated 106 to 150 g/m ² coated 151 to 300 g/m ² uncoated 151 to 300 coated	Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
SRA3 64 to 105 g/m ² uncoated 106 to 176 g/m ² uncoated 106 to 150 g/m ² coated 151 to 300 g/m ² uncoated 151 to 300 coated	Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
Auto Duplex Speeds	Colour	Black and white	Colour	Black and white
A4 Example: 64 to 105 g/m ² uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute
A3 Example: 64 to 105 g/m ² uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Device Specifications				
Monthly Duty Cycle	Up to 300,000 pages. ¹			
Average Monthly Print Volume (AMPV)	10,000 to 60,000 pages per month ²			
Technology	Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			

Xerox® Colour C60/C70 Printer

Accessories			
Optional	Offset Catch Tray Simple Catch Tray High Capacity Feeder (A4) 1 Tray Oversize High Capacity Feeder with Storage Bin 2 Tray Oversize High Capacity Feeder Vertical Transport Kit BR Finisher (requires Vertical Transport Kit) BR Booklet Maker Finisher (requires Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Interface Module Light Production Finisher (requires Interface Module) Light Production Finisher with Booklet Maker (requires Interface Module) Light Production Finisher with Booklet Maker and C Fold / Z Fold Unit (requires Interface Module) GBC® AdvancedPunch™ (requires Interface Module and Light Production Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Light Production Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow Print Server Integrated for the Xerox® Colour C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Foreign Device Interface Kit Mobility Plate Envelope Fuser Kit Right Wing Table Kit USB Hub Kit XMPie® VDP Kit PostScript Kit (recommended for Xerox® Integrated Colour C60/C70 Print Server (DMP) – PostScript Kit not needed with Fiery or FreeFlow Print Servers) VOIP Fax 1 or 3 Line Fax Kits Server Fax Enablement Common Access Card Enablement Kit Xerox® Scan to PC Desktop® Xerox Secure Access Unified ID System®		
Electrical Requirements			
	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
Accessories	Each module requires 220V, 10 A		
Power Consumption			
Running (Average)	C60: 1,052 watts; C70: 1,250 watts		
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 2 min.)		
Low Power Mode Recovery Time	Less than 20 seconds		
Operating Environment			
Required Temperature Range	10 to 28°C (Relative Humidity less than 62.5% when temp is 32°C or less)		
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6 B(A)		
Sound Pressure Levels	Operating: 56 dB(A); Standby: 18 dB(A)		
Weight (approximate base unit only)	273 kg		
Dimensions	Width	Depth	Height
Base Unit with Catch Tray	1,574 mm	803.5 mm	1,391.5 mm
Base Unit with BR Finisher	2,009 mm	803.5 mm	1,391.5 mm
Base Unit with BR Booklet Maker Finisher	2,068 mm	803.5 mm	1,391.5 mm
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	2,301 mm	803.5 mm	1,391.5 mm
Base Unit with Light Production Finisher	2,481 mm	803.5 mm	1,391.5 mm
Base Unit with Booklet Maker Finisher	3,121.7 mm	803.5 mm	1,391.5 mm
GBC® AdvancedPunch™	305 mm	724 mm	978 mm
Xerox® SquareFold® Trimmer	1,066.3 mm	724 mm	558.8 mm
High Capacity Feeder	389 mm	614 mm	377 mm
One Tray Oversize High Capacity Feeder	988 mm	762 mm	992 mm
Two Tray Oversize High Capacity Feeder	988 mm	762 mm	992 mm

Xerox® Colour C60/C70 Printer

Certifications	
	WHQL certification (depending on print server / controller selected) Citrix MEDITECH SAP Common Criteria (undergoing evaluation) ENERGY STAR® ECOLOGO® GS Mark NOM EAC/GOST To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .
Graphic Arts Credentials	
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GRACoL® specifications *Depending on Print Server/Controller selected
Paper Handling	
Single-pass Automatic Document Feeder	
Capacity ³	250 sheets of plain paper – 75 g/m ²
Speed	Up to 200 ipm colour / 200 ipm black and white (2-sided, A4)
Paper Sizes	Custom sizes: A5 to A3
Weights	38 to 200 g/m ²
Bypass Tray	
Capacity ³	Up to 250 sheets
Sizes	Custom sizes: 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)
Weights	64 to 300 g/m ² (uncoated and coated)
Envelope Capacity	30 to 50 envelopes
Envelope Sizes	(Available as Tray 5. Paper Size Default within tools (run flap open at the trail edge)) Custom sizes: 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended
Envelope Weights	75 to 90 g/m ²
Trays 1 to 4	
Capacity ³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets
Sizes	Tray 1: A5 to SRA3 Tray 2: A5 to A3 Tray 3: B5, A4 Tray 4: B5, A4
Weights	64 to 220 g/m ² (uncoated and coated) Trays 1 and 2: up to 256 g/m ² uncoated
Optional High Capacity Feeder (HCF)	
Capacity ³	2,000 sheets
Sizes	184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
Weights	64 to 220 g/m ² (uncoated and coated)
Optional Oversize High Capacity Feeder (OHCF) – 1 or 2 Tray Options	
Capacity ³	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets
Sizes	1 Tray OHCF: 182 x 250 mm (B5) to 330 x 488 mm (SRA3) 2 Tray OHCF: 102 x 152 mm to 330 x 488 mm (SRA3)
Weights	64 to 300 g/m ² (uncoated and coated)
Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversize High Capacity Feeder)
Automatic Two-Sided	<ul style="list-style-type: none"> • 220 g/m² auto duplex includes A4 / A3 / SRA3 • 300 g/m² manual duplex for all stocks from bypass trays and optional Oversize High Capacity Feeder

Finishing	
Simple Catch Tray or Offset Catch Tray	
Capacity ³	500-sheet stacking
Optional BR Finisher (Requires Vertical Transport Kit)	
Capacity ³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) A3 or 200 sets (single-position staple) A4
Sizes	A6 to SRA3 for stacking B5 to A3 for stapling
Weights	64 to 300 g/m ² (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 g/m ² A3, A4, B4 and B5 sizes supported
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Optional BR Booklet Maker Finisher (Requires Vertical Transport Kit)	
Capacity ³	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 / SRA3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3 / SRA3
Sizes	A6 to SRA3 for stacking B5 to A3 for stapling
Weights	64 to 300 g/m ² (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 g/m ² A3, A4, B4 and B5 sizes supported
Hole Punch	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 g/m ² coated or 5 sheets at 177 to 220 g/m ² coated) Bi-fold up to 5 sheets A3, A4, SRA3 supported
Optional C Fold / Z Fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)	
Types	C Fold, Z Fold and Z Half Fold
Capacity ³	40 sheets
Sizes	C Fold and Z Fold: A4 SEF only Z Half Fold: A3 only
Weights	64 to 90 g/m ²
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
Optional Light Production Finisher (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 80 g/m ² , A4 Lower Tray: 3,000 sheets of 80 g/m ² , A4
Sizes	A6 to SRA3
Weights	64 to 300 g/m ²
Multiposition Stapling	Up to 100 sheets of 80 g/m ²
Hole-punching	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity	Capacity: 200 sheets of 128 g/m ² Sizes: A3, A4, B4, B5 Weights: 64 to 220 g/m ²
Decurling	Included with Interface Module and Light Production Finisher Bidirectional with Auto and Manual settings

Xerox® Colour C60/C70 Printer

Optional Light Production Finisher with Booklet Maker (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 80 g/m ² , A4 Lower Tray: 2,000 sheets of 80 g/m ² , A4
Sizes	A6 to SRA3
Weights	64 to 300 g/m ²
Multiposition Stapling	Up to 100 sheets of 80 g/m ²
Hole-punching	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	200 sheets of 128 g/m ² A3, A4, B4, B5 64 to 220 g/m ²
Decurling	Included with Interface Module and Light Production Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 g/m ² (uncoated) Bi-fold up to 5 sheets A4, B4, A3, SRA3
Optional Light Production Finisher with Booklet Maker and C Fold/ Z Fold Unit (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 80 g/m ² , A4 Lower Tray: 2,000 sheets of 80 g/m ² , A4
Sizes	A6 to SRA3
Weights	64 to 300 g/m ²
Multiposition Stapling	Up to 100 sheets of 80 g/m ²
Hole-punching	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	200 sheets of 128 g/m ² A3, A4, B4, B5 64 to 220 g/m ²
Decurling	Included with Interface Module and Light Production Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 g/m ² (uncoated) Bi-fold up to 5 sheets A4, B4, A3, SRA3
Z Fold / C Fold Unit	Folder option provide three different folds: C Fold, Z Fold and Z Half Fold Folding limited to 60-90 g/m ² media only C Fold and Z Fold: – A4 paper sizes only – Output destination to envelope tray only – Max envelope tray capacity- 40 sheets Z Half fold: – A3 paper sizes only – Output destination to stacker tray or top tray
Optional GBC® AdvancedPunch (Requires Interface Module and Light Production Finisher with or without Booklet Maker)	
Punch Configuration Sizes	A4 LEF
Weights	75 to 216 g/m ² (uncoated and coated) Wide selection of slide-in / slide-out GBC punch die sets available
Optional Xerox® SquareFold® Trimmer Module (Requires Interface Module and Light Production Finisher with Booklet Maker)	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 90 g/m ² 5 to 25-sheet booklets (up to 100 imaged sides) at 80 g/m ²
Sizes	Custom sizes: A4 to SRA3
Weights	64 to 300 g/m ²
Convenience Stapler	
Capacity	50 sheets (90 g/m ² media)

Xerox® Colour C60/C70 Printer

Print	
Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
Registration	<ul style="list-style-type: none"> • Advanced registration technology for tighter control • Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity • + 1.2 mm front to back registration
First-print-out Time	PS- A4 LEF Simplex Colour 10.4 seconds / Black and white 8.5 seconds
Print Features	<ul style="list-style-type: none"> • A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing • Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish • Makes mobile printing simpler and more convenient • Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 g/m² • Xerox Extensible Interface Platform® allows you to connect to third-party software solutions that you can access from the touch-screen of the device • Your choice of servers to best fit your environment: <ul style="list-style-type: none"> – Xerox® Integrated Colour C60/C70 Print Server – Xerox® EX-i C60/C70 Print Server Powered by Fiery® – Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer – Xerox® EX C60/C70 Print Server Powered by Fiery® • Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters • Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Copy	
First-copy-out Time	
From the Platen:	As fast as 7.8 seconds colour / 5.1 seconds black and white
From the DADF:	As fast as 9.6 seconds colour / 5.3 seconds black and white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	Auto colour Auto rotation Image shift Edge erase Auto centreing Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages

Xerox® Colour C60/C70 Printer

Special Features	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Annotation Single/Dual colour Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400 % Margin Shift Photo Mode Poster Mode Preset Reduce / Enlarge Programme Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build Job Programme</p>
Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	<p>Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job</p>
Input Speed	Up to 200 images per minute colour and black and white
Resolution	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi</p>
Maximum Scan Area	Originals up to A3
Network Print Services	<p>Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release</p>
File Formats	<p>PDF Image Only PDF (Searchable) PDF (Linearised) PDF (A-1 Level A) TIFF V6 JFIF XPS</p>
Document Management Fields (Metadata)	<p>One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard</p>

Xerox® Colour C60/C70 Printer

Scan Features	<p>Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP Scan via NDS Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Remote Printer Scan to Fax Server Scan to Multiple Destinations Scan to Documentum Scan to DocuShare Scan to Domino Scan to Hummingbird Scan to Interwoven WorkSite Scan to Live Link Enterprise Server Scan to Microsoft Dynamics GP Scan to MS Exchange web folder Scan to Microsoft SharePoint Scan to SharePoint Portal Server Scan to Thompson ProLaw Scan to Tower TRIM Scan to Web URL Scan to Microsoft Network Folder Scan to Exact e-Synergy</p>
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Scan to Email Features	<p>Colour scanning, Auto Colour, Greyscale, Black and white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job</p>
Authentication	<p>SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)</p>
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.
Fax (Optional) – One or Three Line Fax Options	
Compatibility	Colour, Auto Colour, Black and white
Maximum Scan Area	A3 SEF
Fax Send Features	<p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>
Fax Print Features	<p>Print from USB Storage Device Media Print Unicode Printing</p>
Fax Features	<p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>

Xerox® Colour C60/C70 Printer

Device Management	
Xerox® CentreWare® Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Print Services	
Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. (ASR support is subject to local system compatibility and enablement, please contact your local Xerox support team for details or check our capability matrix at http://www.xerox.co.uk/about-xerox/account-management/smart-meter/engb.html)
Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication Xerox Secure Access Unified ID System® IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria (undergoing evaluation)
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions .
Print Server	
Xerox® Integrated Colour C60/C70 Print Server (DMP) (Standard)	
Processor	993 MHz
Memory (ESS)	4 GB RAM
System Disk	320 GB Hard Disk Drive
Display	10.4 in. colour touchscreen flat-panel
Device Operating System	VxWorks
Page Description Languages	PDF XPS®, PCL® 6 emulation HP-GL2 (direct submission) Adobe® PostScript® 3™ option TIFF JPEG

Xerox® Colour C60/C70 Printer

Operating Systems	Windows® XP SP1 & above (32 & 64 bit) Server 2003 / 2008 (32 & 64 bit) Vista (32 & 64 bit) Windows 7 (32 & 64 bit) Mac OS® 10.4 and above Citrix® Custom driver for UNIX: – AIX® 5 v5.3 – HP-UX® 11.0 / 11i v2 – Solaris® 8/9/10 – Linux® Fedora Core® 1/5 – Red Hat® ES4 – SUSE® 10/11
Print Drivers Supported	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit Windows 7 / 2008 32 Bit Windows 7 / 2008 64 Bit (Microsoft certified) Macintosh® OS 10.3.0 and UNIX N/A Bidirectional with Xerox Custom Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver®
Features	<ul style="list-style-type: none"> • Automatic two-sided • Bidirectional Print Drivers provide device and job status • Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) • Secure print • Delay print • Embedded Web server for remote control/monitor/setup • Enhanced Gloss • Sample set • Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks • Banner sheets • Fit to new paper size • Output tray selection • Print calibration • Print from USB Plus more!
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
	For more information, go to www.xerox.com/C70IntegratedColorServer .
Additional Print Server Options	
Optional Xerox® EX-i C60/C70 Print Server Powered by Fiery®	
Processor	Intel® Pentium® G850 Processor, E200, 2.90 GHZ
Memory (ESS)	2 GB
System Disk	500 GB
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	<ul style="list-style-type: none"> • Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and colour-critical PDFs accurately and quickly. • Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. • Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools. • Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70EXiFieryColorServer .

Xerox® Colour C60/C70 Printer

Optional Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer	
Processor	Intel® Dual Core Pentium G3420 Processor
Memory (ESS)	8 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	True Adobe® PostScript® Level 1, 2, 3; Adobe® Acrobat® 9.0, PDF 1.8, PDF/X; TIFF, PCL 5c, PCL 6XL, EPS, JPEG
Features	<p>Simple</p> <ul style="list-style-type: none"> • Windows 7 platform for a familiar experience • Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups • Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) <p>Productive</p> <ul style="list-style-type: none"> • All the advantages of a Xerox Production workflow – delivered in a value-oriented solution • Streamlined drag/drop submission from tablets and more <p>Powerful</p> <ul style="list-style-type: none"> • Bring the power of Xerox® patented RIP technology in a value oriented solution • Latest direct Adobe PDF Print Engine and GC credentials included • Includes Variable Data Print / Colour Management / Production Workflows <p>Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support</p>
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70FreeflowPrintServer .
Optional Xerox® EX C60/C70 Print Server Powered by Fiery®	
Processor	Intel® Core i5-2400, 4 Core, PRO80-IV, 3.10 GHz
Memory (ESS)	4 GB
System Disk	1 TB
Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP
Features	<ul style="list-style-type: none"> • Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colours. This feature also eliminates the need to re-programme jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalised communications and packaging and photo publishing applications. • Fiery ColourWise gives high-quality colour out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Colour Profiler Suite to control and manage colour throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeSequence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation.
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)
	For more information, go to www.xerox.com/C70EXPrintServer .

Xerox® Colour C60/C70 Printer

Supplies	Description	Yield	Part Number
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages ⁴	006R01521
	Cyan	34,000 pages ⁴	006R01524
	Magenta	32,000 pages ⁴	006R01523
	Yellow	34,000 pages ⁴	006R01522
Toner Cartridges (Sold)	Black	30,000 pages ⁴	006R01655
	Cyan	34,000 pages ⁴	006R01656
	Magenta	32,000 pages ⁴	006R01657
	Yellow	34,000 pages ⁴	006R01658
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663
Colour Drum Cartridge	1 Cartridge per Colour	85,000 pages ⁴	013R00664
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650
Fuser	220V	200,000 pages ⁴	008R13065
Waste Toner Container	1 Cartridge	50,000 pages ⁴	008R12990
Staple Cartridges	Finishers and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177
	Waste Container for Light Production Finisher	5,000 each cartridge	008R13041
	Light Production Finisher with Booklet Maker	5,000 each cartridge	008R12925
Staple Refills	Finishers and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput

³ Paper capacities are based on 75 g/m² stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% black and white ratio, using A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

To view a product video, visit www.xerox.com. Build and configure your own Xerox® Colour C60/C70 Printer at www.buildyourownxerox.com.

